


This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		ADDED ASSEMBLY VIEW.	8/31/2006	WP	
2		INSTALLED NEW DRAWING FORMAT, REDUCED FROM 3 PAGES, ADDED LOCTITE NOTE.	9/23/2008	WP	RW
3		-1 CH'D CLEARANCE DIAMETER FROM Ø.656 TO Ø.672. CH'D ENGRAVE NOTE.	5/16/2012	RJC	GE
4		-1 CH'D THRU HOLE WAS Ø.532 IS Ø.484. -3 CORRECTED GUIDE WAS SAME AS RB500N9605-3 IS SAME AS RB500N9505-1M-3.	8/6/2013	RJC	GE
5	16-0206	CH'D TITLE WAS DRIVE SHAFT COUPLER SOCKET ASSEMBLY IS NOTAR FAN NUT SOCKET (MODIFIED). DELETED TOOL USE NOTE. -1 CH'D DIM WAS Ø1.485 +.015/-0.005 IS Ø1.49. WAS .700 IS .70. WAS Ø.672 IS Ø.68. WAS .150 IS 8X .150. WAS Ø.484 THRU $\sqrt{\text{V}}$ Ø.76 X 120° BROACH .500 SQ. IS 2X .508/.503. ADDED MISSING DIM R.13. 2X .670 MIN.. ADDED FINISH SPEC QMSI-6.2.2. B.O. REV D. CH'D MATERIAL WAS 41L40 RND. BAR IS 4140/4142. -3 CH'D DIM WAS Ø.500 THRU IS Ø.500 +.005/-0.000 THRU. ADDED FINISH SPEC QMSI-6.2.2. B.O. REV D. ADDED P/N'S -5, -7, -9 TO BUYOUTS. CH'D -5 DESCRIPTION TO THREAD-LOCKING INSERT.	11/2/2016	RJC	SM



NOTE:



1 LOCTITE INTO -1.

DART AEROSPACE	
TITLE NOTAR FAN NUT SOCKET (MODIFIED)	
DWG NO. RB500N9506-1M	REV 5
MAT'L REAT TREAT FINISH SPEC	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± 5° .X ± .1 SURFACES = 125° ✓
DRAWN BY: CLOUGH	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R
CHECKED: DUERFELDT	2. DIMENSIONAL LIMITS APPLY AFTER PLATING
OPPS APPR: ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
QA APPR: LINDSAY	USED ON MODEL
APPROVED: MACKOVJAK	MD-500N NOTAR
SCALE 1:4	DATE 11/1/2016
SHEET 1 OF 3	


ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			-1	1	SOCKET	4140/4142		2
			-3	1	GUIDE	STRESSPROOF		3
		B/O	-5	1	THREAD-LOCKING INSERT	STEEL	1/2-20 THREAD X 3/4-10 TAP X 21/32 (MCMASTER-CARR #90248A086)	1
		B/O	-7	1	HEX HEAD CAP SCREW	STEEL GRD. 8	1/2-20 X 10 (MCMASTER-CARR #91257A501)	1
		B/O	-9	1	WASHER	STEEL	Ø1/2 X 1-1/4 O.D. (MCMASTER-CARR #94744A289)	1

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
3		-1 CH'D CLEARANCE DIAMETER FROM Ø.656 TO Ø.672, CH'D ENGRAVE NOTE.	5/16/2012	RJC	GE
4		-1 CH'D THRU HOLE WAS Ø.532 IS Ø.484.	8/6/2013	RJC	GE
5	16-0206	-1 CH'D DIM WAS Ø1.485 +.015/-0.005 IS Ø1.49, WAS .700 IS .70, WAS Ø.672 IS Ø.68, WAS .150 IS 8X .150, WAS Ø.484 THRU $\sqrt{\phi .76 \times 120^\circ}$ BROACH .500 SQ. IS 2X .508/.503, ADDED MISSING DIM R.13, 2X .670 MIN., ADDED FINISH SPEC QMSI-6.2.2, B.O. REV D, CH'D MATERIAL WAS 41L40 RND. BAR IS 4140/4142.	11/2/2016	RJC	SM



SECTION A-A






(-1)
SOCKET

DART AEROSPACE	
TITLE NOTAR FAN NUT SOCKET (MODIFIED)	
DWG NO. RB500N9506-1M-1	REV 5
MAT'L 4140/4142	UNLESS OTHERWISE SPECIFIED
HEAT TREAT RC 37-45	DIMENSIONS ARE IN INCHES
FINISH BLACK OXIDE	.XXX ± .005 FRACTIONS ± 1/8
SPEC QMSI-6.2.2, B.O. REV D	.XX ± .01 ANGLES ± 5°
DRAWN BY: CLOUGH	.X ± .1 SURFACES = 125°
CHECKED: DUERFELDT	1. BREAK ALL SHARP EDGES
OPPS APPR: ANDERSON	.015 x 45° OR .015R
QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY
APPROVED: MACKOVJAK	AFTER PLATING
SCALE 1:2	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 11/1/2016	USED ON MODEL
SHEET 2 OF 3	MD-500N NOTAR

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
4		-3 CORRECTED GUIDE WAS SAME AS RB500N9605-3 IS SAME AS RB500N9505-1M-3.	8/6/2013	RJC	GE
5	16-0206	-3 CH'D DIM WAS Ø.500 THRU IS Ø.500 +.005/- .000 THRU, ADDED FINISH SPEC QMSI-6.2.2, B.O. REV D.	11/2/2016	RJC	SM



(-3)
GUIDE

DART AEROSPACE	
TITLE NOTAR FAN NUT SOCKET (MODIFIED)	
DWG NO. RB500N9506-1M-3	REV 5
MAT'L STRESSPROOF	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH BLACK OXIDE	.XXX ± .005 FRACTIONS ± 1/8
SPEC QMSI-6.2.2, B.O. REV D	.XX ± .01 ANGLES ± 5°
	.X ± .1 SURFACES = 125°
DRAWN BY: CLOUGH	1. BREAK ALL SHARP EDGES
CHECKED: DUERFELDT	.015 x 45° OR .015R
OPPS APPR: ANDERSON	2. DIMENSIONAL LIMITS APPLY
QA APPR: LINDSAY	AFTER PLATING
APPROVED: MACKOVJAK	3. INTERPRET DIM AND TOL PER
	ASME Y14.5M-2009
	USED ON MODEL
	MD-500N NOTAR
SCALE 1:1	DATE 11/1/2016
	SHEET 3 OF 3